



EWF POWER PACKS

Excavators



Dozers



Graders



Loaders



Ag Tractors



Reach Top-Level Productivity with Dedicated Extra Power for your Hydraulic Attachments.

Compact design and straightforward installation on excavators, dozers, graders, loaders, ag tractors, or other types of heavy equipment.

DENIS CIMA F

DENISCIMAF.com



Dedicated Power Top-Level Productivity



EWF was developed specifically to increase the power available for your industrial attachments through an independent hydraulic circuit.

Easy to install on a variety of heavy equipment, it is a quick and powerful solution to reach higher level of productivity and profitability.



EWF-100's control panel



EWF-170 and EWF-350's control panel

The power pack is monitored and controlled by the operator through a control panel.

Compact design and straightforward installation on excavators, dozers, graders, loaders, ag tractors, or other types of heavy equipment.

Excavators



Dozers



Graders








Loaders



Ag Tractors



	EWF-350	EWF-170	EWF-100
 Engine	350 hp Cummins 8.9 L Turbo	168 hp Cummins 4.5 L Turbo	99 hp Cummins 3.3 L Turbo
 Hydraulic Flow	379 L/min (100 gal/min)	246 L/min (65 gal/min)	170 L/min (45 gal/min)
 Max Hydraulic Pressure	379 bar (5 500 psi)	379 bar (5 500 psi)	345 bar (5 500 psi)
 Hydraulic tank capacity	133 L (35 gal)	95 L (25 gal)	38 L (10 gal)
 Weight (approx.)	4 082 kg (9 000 lb)	1 130 kg (2 500 lb)	545 kg (1 200 lb)

These specifications are for information purposes only and are subject to change without notice.



TECHNICAL SPECIFICATIONS

DIMENSIONS AND WEIGHTS	EWF-350	EWF-170	EWF-100
Weight	4 082 kg (9 000 lb)	1 130 kg (2 500 lb)	545 kg (1 200 lb)
Height	239 cm (94 in)	107 cm (42 in)	112 cm (44 in)
Width	274 cm (108 in)	122 cm (48 in)	142 cm (56.5 in)
Depth	130 cm (51 in)	130 cm (51 in)	68.5 cm (30 in)

ENGINE	EWF-350	EWF-170	EWF-100
Model	350 hp Cummins 8.9 L Turbo	168 hp Cummins 4.5 L Turbo	99 hp Cummins 3.3 L Turbo
Number of cylinders	6	4	4
Maximum power	350 hp @ 1800 rpm	168 hp @ 2300 rpm	99 hp @ 2600 rpm
Maximum torque	1120 lb-ft @ 1200 rpm	459 lb-ft @ 1500 rpm	306 lb-ft @ 1600 rpm

HYDRAULIC SYSTEM	EWF-350	EWF-170	EWF-100
Hydraulic pressure	379 bar (5 500 psi)	379 bar (5 500 psi)	379 bar (5 500 psi)
High flow	379 L/min (100 gal/min)	246 L/min (65 gal/min)	170 L/min (45 gal/min)
Hydraulic tank capacity	133 L (35 gal)	95 L (25 gal)	38 L (10 gal)

COOLING SYSTEM	EWF-350	EWF-170	EWF-100
Engine	Glycol/air	Glycol/air	Glycol/air
Hydraulic	Oil/air	Oil/air	Oil/air

These specifications are for information purposes only and are subject to change without notice.